

# MATERIAL SAFETY DATA SHEET

## FIRE JACKET REPAIR KIT PART B

### I. 24-HOUR EMERGENCY CONTACT INFORMATION

CHEM-TEL United States ..... 800-255-3924  
International ..... 813-248-0585

### II. HAZARDOUS INGREDIENTS / IDENTITY INFORMATION

Component Identification	CASRN	OSHA PEL	ACGIH TLV	% (by weight)
Ammonium polyphosphate	0068333-79-9	None Established		10 – 25
Limestone	00001317-65-3	None Established		10 – 25
Magnesium silicate mixture		None Established		1 – 10
Tetraethylenepentamine	0000112-58-2	None established		1 – 10
Titanium dioxide	0013463-67-1	None Estab.	10 mg/m <sup>3</sup>	1 – 10

### III. PHYSICAL / CHEMICAL CHARACTERISTICS

Boiling Point ..... 275°F  
Melting Point ..... Not Determined  
Vapor Pressure ..... Not Determined  
Vapor Density (Air = 1) ..... > 1  
Specific Gravity (Water = 1) ..... 1.197  
Evaporation Rate ..... Slower than ether  
pH ..... Not Determined  
Odor Threshold ..... Not Determined

### IV. FIRE and EXPLOSION HAZARDS

Flash Point ..... 392°F (200°C)  
Autoignition Temperature ..... Not Determined  
LEL ..... 1 (%vol in air) at NTP  
Extinguishing Media ..... Foam, Dry Chemical, CO<sub>2</sub>, Water Spray, Water Fog  
NFPA Ratings ..... Health (2) – Flammability (1) – Reactivity (1)

Special Firefighting Procedures: Move containers from fire area if you can without risk. Runoff from fire control may cause pollution. Dike fire control water for later disposal. Do not scatter the material.

Fire and Explosion Hazards: Material may burn but does not readily ignite. Fire may produce irritating, corrosive, and/or toxic gases. Containers may explode when heated.

### V. REACTIVITY DATA

Stability ..... Stable  
Hazardous Polymerization ..... Will not occur  
Conditions to Avoid ..... Excess Heat  
Incompatibilities ..... Oxidizing Materials  
Hazardous Decomposition Products ..... CO, and CO<sub>2</sub>

## VI. HEALTH HAZARD DATA

Route(s) of Entry:           Inhalation..... Yes  
   Skin..... Yes  
   Ingestion..... Not Expected

Acute (Short-Term) Health Effects: *Inhalation:* Harmful if inhaled. Causes nose and throat irritation. Vapors may affect the brain or nervous system causing dizziness, headache, or nausea. *Eyes:* Causes eye burns. Do not get into eyes. *Skin:* Causes skin burns. May be harmful if absorbed through the skin. *Ingestion:* Harmful if swallowed. May cause abdominal pain, nausea, vomiting, diarrhea, or drowsiness.

Chronic (Long-Term) Health Effects: Repeated or prolonged contact with the skin may cause dermatitis, skin sensitization, and possible organ damage.

Carcinogenicity: The NTP (National Toxicology Program), IARC (International Agency for Research on Cancer), and OSHA do not classify any of this product's ingredients as carcinogens.

Signs and Symptoms of Exposure: Signs and symptoms following exposure to this product will generally be related to contact of the material with the skin and can include irritation, redness, and/or burning.

Medical Conditions Generally Aggravated by Exposure: Existing skin disorders may be aggravated upon exposure. Existing respiratory disorders may be aggravated due to inhalation.

### Emergency and First Aid Procedures:

*Inhalation:*           If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention immediately.

*Skin Contact:*       In case of skin contact, immediately flush with soap and plenty of water. Get medical attention immediately.

*Eye Contact:*       In case of eye contact, immediately flush with soap and plenty of water for at least 15 minutes. Get medical attention immediately.

*Ingestion:*           If swallowed, immediately contact Poison Control Center. DO NOT induce vomiting unless instructed to do so by medical provider. Never give anything by mouth to an unconscious person.

HMIS Ratings ..... Health (2) – Flammability (1) – Reactivity (0)

## VII. PRECAUTIONS FOR SAFE HANDLING and USE

Steps to be Taken in Case Material is Released or Spill: If a spill occurs, do not allow spilled materials to enter storm sewers, sanitary sewers, or impact ground water. Place spilled materials in appropriate containers for disposal.

Waste Disposal Method: Disposal must be in accordance with applicable laws.

Precautions to be Taken in Handling and Storage: Keep away from heat sparks and flame. Do not smoke. Extinguish all flames and pilot lights and turn off stoves, heaters, electric motors, and other sources of ignition during use and until all vapors are gone. Vapors may cause flash fire or ignite spontaneously. Prevent build-up of vapors by opening all windows and doors to achieve cross-ventilation. Close container after each use. Do not get into eyes or onto skin or clothing. Wash thoroughly after handling.

## VIII. CONTROL MEASURES

Respiratory Protection: None typically required.

Ventilation: A system of local and/or general exhaust is recommended.

Hand Protection: Gloves impervious to this material should be worn.

Eye Protection: ANSI-approved safety glasses with side shields or chemical goggles.

Other: Such clothing as to minimize or eliminate skin contact.

**IX. REGULATORY INFORMATION (Not meant to be all-inclusive)**

Hazardous Materials Transportation Act (HMTA)

When offered alone, this material should be classified as follows:

Proper Shipping Name ..... Non-Regulated  
 Hazard Class..... Not Applicable  
 Identification Number ..... Not Applicable  
 Packaging Group ..... Not Applicable  
 Label Required..... Not Applicable

When offered with the catalyst within the same container, the classification is:

Proper Shipping Name ..... Non-Regulated  
 Hazard Class..... Not Applicable  
 Identification Number ..... Not Applicable  
 Packaging Group ..... Not Applicable  
 Label Required..... Not Applicable

Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA)

This produce contains the following CERCLA Section 102(a) hazardous substance(s) as listed in 40 CFR 302.4:

Identity	CASRN	% (by weight)	Reportable Quantity (RQ)
None			

Superfund Amendment and Reauthorization Act (SARA)

This product contains the following SARA Title III Section 302 extremely hazardous substance(s) as listed in 40 CFR Part 355:

Identify	CASRN	% (by weight)
None		

SARA Title III Section 311/312 hazardous categorization:

This product has been reviewed according to the EPA hazard categories promulgated under SARA Tile III Section 311 and 312 and is considered to meet the following hazard categories:

- An immediate (acute) health hazard
- A delayed (chronic) hazard

This product contains the following SARA Title III Section 313 toxic substance(s) as listed in 40 CFR Part 372:

Identify	CASRN	% (by weight)
None		

Toxic Substances Control Act (TSCA)

All ingredients are on the TSCA inventory or are not required to be on the inventory.

---

**CATALYST / HARDENER INDEX**

The material described in this MSDS is intended for use with the following:

**FIRE JACKET REPAIR KIT PART B**

Review literature supplied with product or contact NOV Fiber Glass Systems for proper mixing ratios.

---

National Oilwell Varco has produced this brochure for general information only, and it is not intended for design purposes. Although every effort has been made to maintain the accuracy and reliability of its contents, National Oilwell Varco in no way assumes responsibility for liability for any loss, damage or injury resulting from the use of information and data herein nor is any warranty expressed or implied. Always cross-reference the bulletin date with the most current version listed at the web site noted in this literature.

[www.fgspipe.com](http://www.fgspipe.com)

2700 W. 65<sup>th</sup> St.  
Little Rock, AR 72209  
USA  
Phone: 501-568-4010  
Fax: 501-568-4465

25 S. Main St.  
Sand Springs, OK 74063  
USA  
Phone: 918-245-6651  
Fax: 918-245-7566

The logo for NOV Fiber Glass Systems features the letters "NOV" in a bold, sans-serif font. The letter "O" is replaced by a red circle with a white dot in the center, resembling a stylized eye or a fiber optic lens. To the right of "NOV", the words "Fiber Glass Systems" are written in a blue, sans-serif font.

© 2009 NATIONAL OILWELL VARCO  
M3800B – March 2009